



AHTS 60M DP-1 - VOS APHRODITE (3056)



GENERAL	
Place of Build	Fujian South East Shipyard, China
Vessel Type	AHTS
Year Built	2011
Flag	Gibraltar
Call Sign	9V8666
Class	RINA
C - Offshore Support Vessel-Supply Anchor Handling; Fire-Fighting ship - 1 -,Unrestricted navigation,Dynapos AM	

COMMUNICATIONS EQUIPMENT	
HF Radio	Furuno RC-1500-1T 400W
VHF Radio	2 x Furuno
Portable VHF Radio's	3 x Furuno
Satellite Communications (Voice and Fax)	Furuno SAT C
E.P.I.R.B	McMurdo 406
GMDSS Compliance	Area A3

PRINCIPAL DIMENSIONS	
Length Overall	59.25 m
Beam	14.95 m
Maximum Draft	4.95 m
Net Registered Tonnage	503 t
Gross Registered Tonnage	1678 t

NAVIGATION EQUIPMENT	
Radar No. 1	Furuno X-band (21" screen)
Radar No. 2	Furuno X-band (15" screen)
GPS	GP 150
Echo Sounder	Furuno FE 702
Navtex	NX 700
Auto Pilot	Naupilot NP 60
Gyro Compass	Anschutz STD 22
DP System	Kongsberg
Reference System 1	DGPS FUGRO Seastar XP
Reference System 2	DGPS FUGRO Seastar G2

MACHINERY & PROPULSION	
Main Propulsion Number	2
Main Propulsion Type	CAT 3516B Diesel
Total BHP	5150
Propellers	2 x CPP in Fixed Kort Nozzles
Bow Thruster	1 X Kawasaki KT-72B3 - 515 kW
	8 t
Stern Thruster	1 x Kawasaki KT-55B3 - 390 kW
	6 t
Main Generators	2 x CAT C18 350 kW
Shaft Generators	2 x 800 kW
Emergency Generators	1 x CAT 65 kW
Rudders	Standard

DECK MACHINERY	
Tugger Winch	2 x 10 t @ 15m/min
Capstan	2 x 5 t @ 15m/min
Deck Crane	1 x 3 t @ 9 m

Total BHP	
Fuel consumption @ 12 Knots	About 11.5 MT per day
Fuel consumption @ 10 Knots	About 8 MT per day
Fuel consumption @ 8 Knots	About 6 MT per day
Fuel consumption in port	About 0.5 MT per day
Fuel consumption in DP mode	About 6 MT per day
Fuel Type	ISO 8217: 2005 DMA - Marine diesel oil

TOWING & ANCHOR HANDLING	
Bollard Pull	65 t
Winch	Plimsoil Waterfall Type
Line Pull	150 t
Brake Capacity	200 t
Anchor Handling Wire and Towing Wire	100 m and 1000 m x 56 mm
Anchor Handling Wire Capacity	100 m x 56 mm
Tow Drum Capacity	1000 m x 56 mm
Spare Tow Wire Capacity	1000 m x 56 mm
Stern Roller	4.0 m x 1.6 m - SWL 200 t
Tow Pins	2 x Closed Top Type SWL 200 t
Shark Jaws	Shark Jaws - SWL 200 t

CARGO CAPABILITIES	
Fresh Water	360 m ³ @ 100 m ³ per hr at 75 m head
Drill Water	400 m ³ @ 100 m ³ per hr at 75 m head
Fuel Capacity (100%)	535 m ³ @ 150 m ³ per hr at 75 m head
Liquid Mud	378 m ³ @ 70 m ³ per hr
Dry Bulk	4 x 1650 cu ft each, total 6,600 cu ft
Dead Weight	1360 t
Clear Deck Area	350 m ²
Deck Cargo	500 t

LIFE SAVING APPARATUS	
Life rafts	Total: 6 = capacity 150 men
Rescue Boat	25 HP OBM, capacity 6 men

ACCOMMODATION	
Crew	13
Passengers	12
Hospital	yes

EXTERNAL FIRE FIGHTING	
Capacity	FIFI 1 - 2400 cu m per hr
Monitor	2 x 1200 cu m per hr
Throw x Height	120 m x 50 m

This technical specification sheet is subject to change without notice. Whilst every effort has been made to ensure the accuracy of the information presented. No guarantees of accuracy can be given. For enquiries, kindly email us at chartering@it.vroonoffshore.com